IN THE CLAIMS

1-12. (canceled)

13. (currently amended) A gas turbine engine ~~comprising~~system comprising:

a gas turbine engine; and

a thrust link comprising a first connector, a second connector, and a span section extending therebetween, ~~each said thrust link~~said first connector comprising a first side, a second side, and an opening extending therebetween and defined by an inner surface, said inner surface comprising a plurality of threads extending radially outward into said connector opening such that said threads are axially spaced substantially constant along said inner surface, said plurality of threads comprises a first thread portion positioned proximate said first side and initially engaging a threaded apparatus coupled to said first connector, said plurality of threads comprising a ~~cutback configured to reduce stresses induced into said plurality of threads~~cutback, wherein said cutback extends through said first thread ~~portion.~~portion, said first connector coupled to said turbine engine, said cutback configured to reduce stresses induced into said plurality of threads.

DO NOT ENTER JM 1/21/05

14. (currently amended) A gas turbine engine system in accordance with Claim 13 wherein ~~each~~ said thrust link connector opening has a center axis of symmetry extending from said connector first side to said connector second side, said cutback oblique with respect to said center axis of symmetry.

15. (currently amended) A gas turbine engine system in accordance with Claim 14 wherein each said thread comprises a crest and a root, said cutback extending through said first thread portion crest.

16. (currently amended) A gas turbine engine system in accordance with Claim 15 wherein said thrust link connector first thread portion is positioned adjacent at least one of said connector first side and said connector second side.